



Synthetic
LABORATORIES, INC

Building & Facility Maintenance

FLOOR CLEANING



Floor Scrub HD

Heavy Duty Low Foaming Floor Cleaner

CORE 3

Core 3: Personal Attention

Every customer requires special attention and has their own demands put on them. Our staff will design and implement a program designed to fit your needs.

Core 3: Experience

With our full staff of formulators, chemists, & marketing professionals we have been bringing cutting edge products to market for over 70 years.

Core 3: Technology

Through daily contact with industry professionals, we are continuously updating and improving our products to make sure you perform at your best.



Synthetic Labs offers industry-leading solutions for businesses and professionals who demand exceptional results.

FLOOR CARE

Floor Scrub HD

Heavy Duty Low Foaming Floor Cleaner

What is Floor Scrub HD?

A heavy duty caustic fortified low foaming floor cleaner that is perfect for removing the toughest soils. It has been fortified with cutting edge low foaming detergents and sodium hydroxide giving it the ability to cut through the heavy grease and soil deposits. Great for use in auto body and mechanic shop floors to remove the heaviest of buildup. This versatile product can be used in a wide variety of applications, ranging from auto scrubbers to mopping.

Benefits:

- Removes the heaviest soils.
- Leaves floors bright and shiny.
- Low foam formula makes it perfect for use in auto scrubbers and rotary machines.
- Fortified with Sodium Hydroxide.
- Removes heavy grease and oils from deep cracks and imperfections in almost any floor.
- Special easy rinsing formula.

Instructions:

Before using, make sure that the desired surface is cool to prevent early evaporation. Read MSDS and test in a small inconspicuous area. For professional use only by trained personnel.

Dilute 50-60:1 for light soils , 40:50-1 for moderate soils, 20-40:1 for heavy soils.

FLOOR SCRUB MACHINES:

Equip machine with aggressive brushes such as steel wire and fill reservoir with cleaner. Double-scrub procedure will give best results. Lay down solution with scrubbing action and allow solution to remain on surface 5 minutes - then lower squeegee blade, scrubbing again and pick up.

CONVENTIONAL ROTARY FLOOR MACHINE:

Equip machine with aggressive brush such as steel wire. Spray, mop or spread cleaner on surface. Scrub area and allow to remain 5 minutes. Scrub again and pick up soiled solution with wet-vacuum or mop.

MANUAL CLEANING:

Apply cleaner by spray mop or sponge and follow by aggressive double brushing or scrubbing. Pick up soiled solution with wet-vacuum, mop or wiping.

Tech Specs:

Color.....	Green
Fragrance.....	Faint
Form.....	Liquid
Phosphates.....	None
FlashPoint.....	212F
pH.....	14
Specific Gravity.....	1.05
Viscosity.....	Thin
Foam.....	Moderate
Biodegradable.....	100%
Shelf Life.....	1 Year

Available Packages

0360-275	275 Gallon Tote
0360-55	55 Gallon Plastic Drum
0360-30	30 Gallon Plastic Drum
0360-15	15 Gallon Plastic Drum
0360-5.25	2x2.5 Gallon Jugs
0360-5	5 Gallon Plastic Pail
0360-4	4 Gallon Case
0360-2L	4x2Liter EZ Fill



Toll Free: 800-255-4050

24 Victory Lane, Dracut, MA 01826

www.syntecpro.com