



Building & Facilities Maintenance Solutions



FOR
INDUSTRY

DuraGuard 25

High Solids High Gloss Floor Finish

CORE 3

Personal Attention

Every customer requires special attention and has their own demands put on them. Our staff will design and implement a program designed to fit your needs.

Experience

With our full staff of formulators, chemists, & marketing professionals we have been bringing cutting edge products to market for over 70 year

Technology

Through daily contact with industry professionals, we are continuously updating and improving our products to make sure you perform at your best.



Synthetic Labs offers industry-leading solutions for businesses and professionals who demand exceptional results.

FLOOR FINISH

DuraGuard 25

High Solids High Gloss Low Maintenance Floor Finish

What is DuraGuard 25?

A premium floor finish that quickly builds a deep, "wet look" gloss that lasts for weeks. DuraGuard 25 has been designed to be extremely durable in order to maintain its high gloss finish for an extended period of time. Will respond beautifully to conventional, high, or ultra-high speed floor equipment after weeks of wear and traffic when used with spray buff or mop-on restorer.

The DuraGuard floor program meets all ASTM standards for slip, detergent, and soil resistance.

Benefits:

- Long lasting durable finish.
- Provides High Level Professional Gloss.
- Responds well to low and high maintenance floor care programs.
- Stands up to high traffic, frequent burnishing and repeated scrubbing.
- Economical Low Maintenance.
- Enhanced Slip Resistance.

Instructions:

Prepare the Surface

Clean the floor thoroughly to remove any dirt, dust, or debris. Strip off any old finish using a floor stripper if needed.

Apply the Finish

1. Pour the acrylic finish into a clean bucket.
2. Use a clean mop or applicator to apply a thin, even coat of the finish.
3. Start in a corner and work your way out of the room in a "W" pattern for even coverage.
4. Allow the first coat to dry completely before applying a second coat if necessary. (Usually 20-30 minutes)
5. Apply 2-4 Coats

Tech Specs:

Color.....White
 Fragrance.....Characteristic
 Form.....Liquid
 Phosphates.....None
 FlashPoint.....212F
 pH.....7-8
 Specific Gravity.....1.03
 Viscosity.....Thin
 Foam.....None
 Biodegradable.....100%
 Shelf Life.....1 Year

| Available Packages | |
|--------------------|------------------------|
| 2646-275 | 275 Gallon Tote |
| 2646-55 | 55 Gallon Plastic Drum |
| 2646-30 | 30 Gallon Plastic Drum |
| 2646-15 | 15 Gallon Plastic Drum |
| 2646-5.25 | 2x2.5 Gallon Jugs |
| 2646-5 | 5 Gallon Plastic Pail |
| 2646-4 | 4 Gallon Case |



Toll Free: 800-255-4050

24 Victory Lane, Dracut, MA 01826

www.syntecpro.com