



FLOOR FINISH

DuraGreen

Zinc Free Floor Finish

CORE 3

Personal Attention

Every customer requires special attention and has their own demands put on them. Our staff will design and implement a program designed to fit your needs.

Experience

With our full staff of formulators, chemists, & marketing professionals we have been bringing cutting edge products to market for over 70 year

Technology

Through daily contact with industry professionals, we are continuously updating and improving our products to make sure you perform at your best.



Synthetic Labs offers industry-leading solutions for businesses and professionals who demand exceptional results.

FLOOR FINISH



Dura Green

Zinc Free Floor Finish

What is DuraGreen?

This environmental preferable metal free floor finish contains no zinc or other heavy metals that can be harmful to waste treatment plants. The low odor finish has exceptional durability and flexibility and can be maintained with scrub and recoat procedures, spray buffering or high speed burnishing.

*** This product meets Green Seal™ Standard GS-37 based on effective performance, concentrated volume, minimized/recycled packaging and protective limits on: VOCs and human & environmental toxicity. GreenSeal.org. Improper use or dilution may lead to increased risk of health effects. Please follow label directions.**

Benefits:

- Long lasting durable finish.
- Provides High Level Professional Gloss.
- Responds well to low and high maintenance floor care programs.
- Stands up to high traffic, frequent burnishing and repeated scrubbing.
- Economical Low Maintenance.
- Enhanced Slip Resistance.
- Green Seal Certified.

Instructions:

Read entire label before using this product.
Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

INITIAL APPLICATION (3-5 coats):

Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surfaces must be clean, dry and free of residue before finish is applied. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or application system. Allow each coat to dry thoroughly before applying additional coats, usually 30-40 minutes.

Tech Specs:

Color.....	White
Fragrance.....	Characteristic
Form.....	Liquid
Phosphates.....	None
FlashPoint.....	212F
pH.....	7-8
Specific Gravity.....	1.04
Viscosity.....	Thin
Foam.....	None
Biodegradable.....	100%
Shelf Life.....	1 Year

Available Packages	
4600-275	275 Gallon Tote
4600-55	55 Gallon Plastic Drum
4600-30	30 Gallon Plastic Drum
4600-15	15 Gallon Plastic Drum
4600-5.25	2x2.5 Gallon Jugs
4600-5	5 Gallon Plastic Pail
4600-4	4 Gallon Case



Toll Free: 800-255-4050

24 Victory Lane, Dracut, MA 01826

www.syntecpro.com